

CD1500 CONTAINER DRYER TYPE 2

kW: 72kW
Remote Access Connection Avail.: Yes
Length (mm): 6000
Height (mm): 2700
Width (mm): 2500
Control Panel (mm): 400
Plug Connection Included: No

Structure: Insulated structure, doors and ceiling:
Polystyrene insulation sandwiched between white CHROMADEK® (0.6mm) faceplate both sides, one entrance, one exit, housed in a refurbished container

Airflow: Galvanised cased axial fans with high-speed Class H 3 phase (380v) motors and aluminium impeller and blades

Heating: 24 x 3kW Electric elements mounted to a treated mild steel bank

Trays: 240
Tray Area (m²): 129,6
Installation Required: Yes
Assembly Required: Yes, Pre-assembled
Weight: 4500kgs
Manual: Included
Training Material: Included
No. Fans: 3
No. Elements: 24
Portable / On Wheels: No

Electrical panel: Equipped with isolator, circuit breakers, fan contactor and overload, heater contactor, overheat safety thermostat, over/under voltage monitor, emergency stop, PLC with pre-loaded software, temperature and humidity sensor, digital timer, UPS, inlet and exhaust damper

Conversions Available:
Electric, Solar, Gas, Hot Water, Turbine

